



# **CWT SPECIFICATIONS**

## Cabinet and Pedestal

Dimensions (H x W x D) Construction Paint Compliance

### **Electrical Data**

Solar Operation Power (Optional) Consumption Mains Operation One Heater Two Heaters **Battery Operation** 

#### **Environmental Conditions**

Operating Temperature\* Heating

\*Relative Humidity up to 97%

#### Operation

Function Buttons

Display

Appl. & Data memory

Near Feld Communication

Card Payment

Magstripe

Contactless

60.5" x 16" x 11.8" LDX Stainless Steel and Aluminum 165-187lbs.

Powder-Coated with Anti-Graffiti Paint En12414

0.4 A

12V, 10.W 230 V

115 V

0.5 A 1 A 2 A

1 A 12 V DC

0.2 A

-31° to 158°F

High Effciency Heater with Thermostat. (Only Available with Main Power)

4 Software Controlled Buttons Below Display Separate Accept and Reject Buttons Alpha Numeric Keyboard with up to 48 Buttons

Graphical, Monochrome, 6.6" Supports Various Alphabets Sdcard up to 4GB

Contactless Card or RFID Tag for Electronic Lock and Access and Cale Online Permit

Insertion Reader for Track 2 with Various Online Processing Services.

Mifare DES Firesmart Card Support Also used for Electronic Lock access and Cale Online Permit Account Service Coin System Coin Verifier

Coin Slot Protection Escrow Volume Coin Box Volume

Coin Vault Locks Coin Vault Door

Auditticket Coin Vault

Printer

Type Capacity Characters Paper Cutter Ticket Sensor Graphics Orientation Paper Supply Black Mark Ticket Length Paper Thickness Paper Loading

Communication 3G,GPRS, LAN, Wi-Fi Type of Data

Miscellaneous Mounting Frame

Electronic Locks

Buzzer Audio

LED Light Vibration Detector

**Central Administration** Software

Industry Standard for up to 16 Coins/Tokens, 3 switch Controlled, Reprogrammable Tolerance Ranges Mechanical Coin Slot Shutter with Inductive Loop 0.35L, 1.8foz

4.6L 155.5foz with Presence Sensor SW Controlled Overfill Protection Closed Cash Collection System Supported

Abloy Exec. 6mm (0.24") Hardened Steel, 4-Way and 6 Points, Drilling-Protected Locking Latches

Supported 4mm (0.16") Sheet Metal with Side Drilling Protection

Thermoelectric Up to 4,500 per Roll Proportional Font, up to 25 chars/line Complete Cutting Take Supported Landscape and Portrait 57mm (2.24"), from Roll Supported 75-150mm(2.95-5.90") 55-110g/m Automatic

Transactions, Blacklists, Tariffs, Parameters, Statistics, SW, OS, Firmware Alarms, Etc.

The CWT Compact is Compatible with Base Anchors Supplied by Cale and Various Terminal

Patented Cale Technology with Central Administration and Both Electronic and Mechanical Opening Mechanisms

Supported Multi Language Audio Support with Pre-Recorded Messages or Sounds for Press of Button, Panals, Popups etc.

Supported Cale WebOffice

Supported



AMERICA

(630) 241-1984 or sales@totalparking.net Total Parking Solutions, Inc. 2721 Curtiss St. Downers Grove, IL 60515

For more information, please contact the Sales Team at: